

A computer vision as a tool for automated quality control in smart manufacturing

Olha Suprun^{1*}, Denys Korotin², Kateryna Kravchenko³, Georgii Goriachev⁴, Arsenii Tverdokhlib⁵

¹ Department of Theory and Technology of Programming, Taras Shevchenko National University of Kyiv, Ukraine

² Department of Computer Engineering, Educational and Scientific Institute of Information Technologies, State University of Information and Communication Technologies, Ukraine

³ Department of Vocational Education and Technologies, according to the Profiles, Pavlo Tychyna Uman State Pedagogical University, Ukraine

⁴ Department of System Analysis and Information Technologies, Vinnytsia National Technical University, Ukraine

⁵ Department of Computer Engineering, Educational and Scientific Institute of Information Technologies, State University of Information and Communication Technologies, Ukraine

*Corresponding author E-mail: o.n.suprun@gmail.com

Received Oct. 5, 2025

Revised Dec. 12, 2025

Accepted Dec. 19, 2025

Online Jan. 2, 2026

Abstract

Computer vision (CV) has emerged as one of the most significant enablers of intelligent factoring system quality control, automated in the context of the AI revolution in the industrial setting today. In this research, we discuss how CV-based architecture can be applied to achieve real-time, adaptive, and scalable quality assurance. This is new research because it is an amalgamation – the evaluation of different mathematical models and artificial intelligence (AI). Deep learning, transfer learning, Bayesian networks, and edge computing are among the solutions, as are fog-cloud partnerships and their direct impact on manufacturing output, productivity, and decision-making efficiency. The article provides comparative data on the performance of other CV frameworks in different industrial conditions by critically examining the new case studies. The practical implications are recommendations for adopting vision-driven systems to improve product consistency, increase human-machine interaction, and reduce operational downtime. In addition, the paper identifies shortcomings in computational resources, system compatibility, and information security that should be addressed in the next generation of smart factories.

© The Author 2026.
Published by ARDA.

Keywords: Computer vision, Deep learning, Smart manufacturing, Continual learning, Adaptive computational architectures

1. Introduction

The current digital revolution in manufacturing, commonly known as Industry 4.0, is driving irreversible changes in the conceptualization of products, their production, and inspection [1]. The core of this development is the implementation of artificial intelligence (AI), machine learning (ML), and computer vision (CV) on production chains [2].

This work is licensed under a [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/) (<https://creativecommons.org/licenses/by/4.0/>) that allows others to share and adapt the material for any purpose (even commercially), in any medium with an acknowledgement of the work's authorship and initial publication in this journal.



The technologies are also actively utilized to automate quality control, increase the efficiency of resources, and reduce the level of human error to overcome the hardships of the traditional inspection technologies that, in addition to being labor-intensive, are unable to meet the requirements of the current manufacturing processes, which are both voluminous and intricate [3].

The contemporary manufacturing environment (also known as a smart factory) comprises the industrial Internet of Things (IoT), cyber-physical systems (CPS), and enhanced data analytics [4]. These interrelated systems require real-time, flexible, and reliable quality assurance plans [5, 6, 7]. The usage of progressive mathematical models and AI-based CV can offer fast, exact examination of graphic data, allowing imperfection recognition, process monitoring, and prognostic upkeep [8, 9]. However, this kind of technology is accompanied by difficulties for its implementation in the current engineering systems in exercise [10, 11]. The problems of computational supply provisions, data association, and system fidelity, as well as the current necessity to familiarize with fluctuations in production limitations, persist to be dominant concerns as the manufacturing continues to modify [12]. The study [13] debates the phenomenon of computer vision-based value control in practical submissions across productions. It breaks down the precise AI models and mathematical resolutions, emphasizing such structures. It studies the computer hardware and software organization in exercise – reflect advantage devices, fog computer science, cloud platforms, and the rest of the toolkit [14].

The problems and operational specifics that arise every day as we scale CV resolutions were also studied [15]. The following passages frame the study plan, analyze the results of real-world smart engineering applications, and reflect on the suggestions for the upcoming of smart engineering and its value administration policy [16]. Although much literature has appeared on CV applications in industrial automation, most previous studies adopt either isolated methods or implement them in a single domain, without incorporating multiple architectures and evaluation measures.

The original idea of the research is a multi-perspective analysis integrating mathematical modeling, an AI-based decision system, and a hardware architecture into a single smart manufacturing system [17]. This method allows obtaining a holistic view of the effects that deep learning, transfer learning, and edge/fog/cloud infrastructures have on the operational reliability, data efficiency, and real-time adaptability. Therefore, the current research addresses a gap in the literature on AI theoretical frameworks and their practical use in full-scale industrial quality control systems.

2. Research method

This paper systematically reviews several sophisticated vision applications in the smart manufacturing setting, based solely on recently published peer-reviewed and preprint sources. It is discussed using case studies and experimental tests, all of which apply modern AI and machine learning to automate quality control [18].

The cases reviewed include:

- The integration of machine learning and fog computing for scalable, real-time quality assurance in industrial settings;
- The utilization of deep learning and transfer learning strategies for defect detection, particularly under data-scarce conditions – addressing challenges like surface inspection and the generalization of models to unfamiliar components;
- Edge-cloud collaborative frameworks that employ large-scale vision models to support adaptive robotic visual inspection [19];
- Convolutional neural networks (CNN)-driven approaches for object detection and tracking, aimed at analysing capacity constraints and productivity across assembly lines [20];
- The application of Bayesian deep learning for uncertainty quantification and automated quality control in image segmentation tasks [21].

The areas of CV focused on in these case studies for further analysis are depicted in Figure 1.




Figure 1. CV areas focused for analysis

Each case study is critically analyzed along several axes:

- **Mathematical and AI/ML techniques:** the comparison models, like CNNs, transfer learning, and uncertainty quantification, and their methodologies of training and inference;
- **Hardware and architectural:** the architecture (edge, fog, or cloud), hardware requirements, and how they integrate into the existing automation systems;
- **Operational effectiveness:** performance measures that are realized in the real-world environment, system adaptability, scalability, and the ability to solve a practical manufacturing challenge, such as data imbalance, latency, and process variability;
- **Quality control mechanisms:** how the computer vision systems become of satisfactory quality, screen, estimate ambiguity, and provide decision provision to any human workers or computerized systems.

This is a criterion-based, inclusive method that allows this study to propose sophisticated visions about the existing scenery of automatic quality control in smart engineering, while also demonstrating both physical advancement and current difficulties in the arena. The scientific works segment demonstrates that there has been substantial progression in the use of CV in engineering quality assurance. Yet, a critical assessment shows that there have continuously been problems with scalability, interpretability, and system flexibility. For instance, most CNN-based resolutions attain high exposure correctness but necessitate large marked datasets and considerable computing resources, which are not possible for small- and medium-sized producers.

Transfer scholarship approaches can overwhelm data lack but tend to fail at field simplification when new flaw types or product geometries arise. Edge-cloud cooperative models improve answer rapidity but raise data synchronisation, bandwidth dependence, and cybersecurity subjects.

On the conflicting, deep knowledge models that include Bayesian methods familiarize vagueness, attractive result consistency, but also cumulative processing dormancy. The paper classifies these gaps and seeks to mix their own rewards into an investigative outline for smart engineering.

The study demonstrates the necessity for cross, resource-sensitive CV schemes that equilibrium correctness, flexibility, and efficacy crossways a wide range of industrial environments. These axes of analysis are presented graphically in Figure 2.




Figure 2. Axes/factors for analysis of case studies

3. Results and discussion

3.1. Deep learning and fog computing for industrial quality control

The paper is a systematic review of various CV applications in intelligent manufacturing, based on published studies and recent preprints. A smooth transition between case studies also enhanced continuity. Putting sophisticated computer vision in a factory quality control system is a traditional tradeoff: the computational complexity of modern deep learning models and the real-world constraints of factory computer systems. For this, a fog computing layer was proposed between traditional direct control systems (PLCs) and supervisory platforms (SCADA). This middle-layer fog bridges the gap between raw machine control and higher-level monitoring, making it a convenient target for advanced AI workloads. Analytically speaking, by decentralizing computational burden and reducing latency between sensors and controllers, fog computing improves smart manufacturing.

CNN-based defect recognition can be integrated into fog nodes, enabling quicker decision-making near the production line and reducing the amount of information sent to the cloud. This construction has gone a extended way in the amount and correctness of fault uncovering enhancement.

Yet, the placement of fog creates some problems in reserve organization, as a piece of fog bulge must be upheld, coordinated with the software program, and supervised for safety. Inside the outline of smart engineering, this method allows real-time graphic analytics but also needs system independence – a crucial necessity for making receptive and maintainable manufacturing places.

3.1.1. Mathematical and AI/ML methods

Essentially, engineering examination grounded on deep learning normally utilizes convolutional neural nets, which are qualified to identify patterns and notice faults from instrument data or images [22]. In real-time requests, implication must be achieved as near to the data basis as possible, needful the positioning of high-performance strategies (often GPUs or FPGAs) on-site [23].

These models are varied and multifaceted, which can be explained by the number of defects and production cases. In most instances, accurate inspection may require extensive inspection using various models or sensor-fusion approaches that combine the various source inputs [24].

3.1.2. Architectural and hardware implementation

Fog computing addresses the constraints of resource-constrained PLCs and the latency issues of cloud-based solutions [25]. Manufacturers can reduce the low-latency and high-throughput requirements of deep learning inference by deploying micro-datacenters, known as fog nodes, near industrial equipment. These fog nodes bundle services as computational resources and facilitate dynamic allocation, fault tolerance through redundancy, and reconfiguration in response to production requirements [26]. Architectural subjects involve real supply use in order to safeguard real-time presentation, setting up the fog layer to sustain correct task assignment and control, and by means of virtualization (containers or lightweight VMs) to achieve rapidity and software program remoteness. More prominently, the complexity of the fog allows the usage of accessible switch systems and progressive CV and machine learning without producing important disturbances to the structure's legacy [27].

3.1.3. Operational effectiveness

The fog-based computer science model signifies an important alteration in the grading process for deep learning-based quality review on dispersed machines. This method is highly relevant to split fixed explanations, as it radically decreases administrative difficulty and working disorganizations by unifying management [28]. Additionally, it provides constant, adaptive modification of machine learning models – an indispensable feature given the integrally investigative nature of manufacturing data science and the vigor of the present-day engineering scenery. Essentially, this plan unifies fragmented quality control systems into a unitary, reactive, and futuristic system [29, 30].

3.2. Transfer learning and data enhancement for defect detection

One significant difficulty in applying deep learning to the quality control task is the need for large, labeled datasets to develop effective models. In practice, especially where new products are inspected or infrequent defects are to be inspected, it is not realistic to assemble such datasets.

To overcome this drawback, Mih et al. propose the TransferD2 system – a transfer learning model designed for defect detection in smart manufacturing under conditions of scarce data and the need for high generalization. Transfer learning improves a model's flexibility by leveraging large-scale pretrained networks (e.g., ResNet or Inception). The key benefit of it in smart manufacturing is that it minimally shortens training time and enables swift adaptation to new production lines. Transfer learning has been shown to achieve better generalization than traditional CNNs, especially when the available dataset is small.

However, it can be biased or less accurate when used with other industrial materials because it relies on the information of the source domain. In practice, the methodology hastens deployment cycles and sustains improvement cycles, which are paramount in contemporary smart factories that aim for just-in-time quality control.

3.2.1. Mathematical and AI/ML approaches

TransferD2 applies pre-trained deep neural network models, including Xception, ResNet101V2, and InceptionResNetV2, that are trained on large-scale datasets such as ImageNet. These networks are used as feature extractors or as starting points for subsequent training. To reduce class imbalance and improve model robustness, standard data augmentation methods, such as random rotations and flips, are applied during training. This is done to achieve more balanced, diverse data to enable the model to learn effectively [31].

First, the original images are split into smaller tiles, each labeled as either defective or non-defective [32]. Data increase tackles, such as accidental revolution and tossing, are used to improve dataset strength and decrease class inequity. In a model exercise, a method named transmission education is used: models are modified on this increased dataset by means of the last few layers of the model. The classifier is then skilled as a binary indicator to favor defective and non-defective slats.

In this stage, the classifier is tested on hidden information from the goal domain. It examines image slates and produces pseudo-bounding boxes to highlight areas likely to cover flaws [33]. It is important to note that the depth of the neural network is not the primary determinant of performance. Instead, associating learned representations of features and defect characteristics and performing data augmentation are essential for optimal functioning. Interestingly, the results reveal that the depth of the neural network is not the primary determinant of the performance. Instead, the correspondence between the feature representations learned and the defect characteristics, as well as the effectiveness of data augmentation, are critical factors in achieving optimal results.

3.2.2. Architectural and hardware implementation

The TransferD2 workflow is very flexible and enables adaptation to new product lines or a large number of defects with minimal additional data. It is trained on standard GPU-based workstations and can be deployed at the edge or with automation systems.

3.2.3. Operational efficacy

Empirically, high accuracy (95.72% on source) is shown in terms of operational effectiveness. Datasets and 91 per cent on-target datasets, even with a small number of labeled samples available. These attributes make TransferD2 a good candidate for the environment where it needs to be deployed and adapted quickly. Its performance has been validated in practice for paint inspection, where it has generalized across different object geometries and materials.

3.3. Large vision models and edge-cloud collaboration of robotic inspection

Contemporary production lines cannot be called fixed in any way – parts design changes often, the lighting system varies, etc., and flaws manifest themselves at random. It no longer suffices to rely on old models of rigid vision; their performance declines swiftly in such changing environments. Together with LAECIPS, a flexible edge-cloud management model came. This would be founded on lightweight models organized through lithe.

The advantage of real-time submissions, while higher-performance, bigger models of visualization track in the cloud in response to multifaceted tasks. It is a smart cooperation amid speed and correctness that fits the modern, continually altering production settings. The teamwork model of advantage and cloud calculation is a sensible method that is straight helpful to intelligent engineering as it is fast and precise. Edge devices complete instant, repetitive tasks, while the cloud handles graphic implications. An active division of labor, such as that, decreases network mobbing and supports big data graphic analytics.

The greatest and important benefit is continuous learning, as the cloud model frequently amplifies edge devices, permitting systems to familiarize with original malfeasances or climate fluctuations. The most

important difficulties, however, are safeguarding proper network connectivity and managing latency-sensitive requests in data-intensive milieus.

3.3.1. Mathematical and AI/ML approaches

The LAECIPS construction structures a "large/little" supportive architecture that influences advantage and cloud incomes. Initially, shallow convolutional neural nets, which are frivolous replicas, perform normal implication tasks straight on edge plans, such as robot supervisors, to deliver low dormancy.

When the edge model obtains contributions that are principal to vague or low-confidence forecasts, doubt metrics are used to specify these bags [34, 35]. These more stimulating cases are progressive to an influential, cloud-based idea perfect (such as the Segment Anything Model or a parallel progressive system), which can attain better correctness, particularly when challenged by uncommon or experimental irregularities [36].

Additionally, LAECIPS also comprises a self-adjustment and continuous learning device. The edge model is rationalized occasionally based on response and the cloud model's outputs, and safeguards steadiness in the face of new data supplies or environmental differences. This cyclical procedure contributes to the model's continuousness and constancy in unbalanced working environments [37, 38].

3.3.2. Architectural and hardware implementation

The architecture can distinguish the use of big and small models and deliver linked incorporation. This design allows most real-time choices to be made at the advantage, minimizing both dimensions and announcement stay. High-capacity cloud models are involved lone when needed, thus endorsing effective use of computational resources [39].

3.3.3. Operational effectiveness

LAECIPS establishes considerable improvements in both correctness and dispensation speed when used to real-world robotic semantic division responsibilities, outdoing conservative edge-only and cloud-only agendas [40]. It is influential in active settings where the review standards and data supplies change regularly, and it needs both high quantity and elasticity.

3.4. Real-time object recognition for capacity constraint study

The usage of computer vision is far more than recognizing faults; it is also vital for examining processes and classifying blocks and output limits on the shop floor. It has been discovered by applying CNN-based object finding and tracking models to examine the dimensions limits within a wheelchair meeting ability [41]. The request for real-time object discovery turns manufacturing management into a data-driven procedure.

Through YOLO-based methods, producers will be able to track disorganizations, apparatus use, and indolent periods with very high chronological determination. This competence not only improves manufacturing competence but also delivers it with usefulness. Data concerning planned decision-making in relative to the distribution of labor and optimization of the plan. Through such a system, unformatted visual info can be transformed into illegal intellect in a smart engineering milieu.

3.4.1. Mathematical and AI/ML tactics

Such a procedure is founded on the YOLO (You Only Look Once) model, one of the greatest methods for object awareness. The reversion problem is resolved by means of a single-stage discovery method. The modern one, YOLOv8, is selected for this reason. There was uncountable rapidity and accuracy [42]. It is worth noticing that YOLOv8 offerings are anchor-free and dissociate forecasts. It is an object-oriented organization and reversion outline that influences high-order loss purposes, such as the whole loss. Rail connection Over Union and Distribution Focal Loss [43]. Such novelties allow the organization to notice and path matters (chairs, workers, and others) crossways video edges and to originate suitable chronological metadata, counting workstation dwell times, station-to-station changes, and idle eras [44].

3.4.2. Hardware and architectural application

In terms of application, the answer is not hostile and trusts on above cameras and a GPU. The enhanced servers of implication. It is combined with the present engineering implementation structures (MES) by means of API termini, supporting real-time analytics and imagining [45].

3.4.3. Operational efficacy

The effect on the operations is immense. The system provides practical information on individual workstation nonproductivity (e.g., that Station C was at only 70.6% productivity over the six months), non-busy and idle times, and unproductive time due to a lack of materials. This is a data-driven strategy that enables more granular capacity planning, improved labor management, and broader process optimization – capabilities that have become increasingly important in the post-pandemic production environment.

3.5. Bayesian deep learning for uncertainty estimation and automated quality control

One persistent challenge in automated quality control is the absence of reliable and absolute measures of model confidence or uncertainty [46]. This issue is particularly acute in high-stakes domains such as medical device manufacturing, where misclassifications can lead to serious consequences. To address this issue, Bayesian QuickNAT was introduced as a fully convolutional neural network for whole-brain segmentation that integrates structure-based uncertainty measures into an automated quality control framework. Bayesian deep learning enhances quality assurance by explicitly quantifying uncertainty, thereby enabling decision-making based on model confidence in high-stakes domains such as aerospace and medical device manufacturing. However, its probabilistic interpretation often requires partial human involvement, which may introduce ambiguity and reduce reliability compared to fully automated systems. A further limitation is its high computational complexity, as ensemble-based approaches, including Monte Carlo dropout, demand additional inference passes and increased processing resources. Despite these drawbacks, Bayesian deep learning remains valuable for explainable AI, as it supports traceability and auditability, which are fundamental principles of smart manufacturing governance.

3.5.1. Mathematical and AI/ML methods

The use of Monte Carlo (MC) dropout in inference, which is the core of this technique, is an intuitive way to treat the neural network as a Bayesian model [47]. This model can achieve this by keeping dropout layers active during test time and running several stochastic forward passes, effectively sampling the posterior distribution over possible segmentation outputs.

This permits the calculation of voxel-based and structure-based uncertainty measures: entropy on MC samples provides finer-grained voxel-level uncertainty maps, as well as summary statistics including the coefficient of variation, pairwise Dice scores, and intersection-over-union measures, providing uncertainty at the regional or structural level [48]. The ensuing measures of uncertainty are strongly related to true segmentation precision (as compared to manual annotations based on Dice scores). Automated quality control is made possible by this correlation, effective scan-level triage, and more powerful group-level analysis [49].

3.5.2. Architectural and hardware implementation

Bayesian QuickNAT is an extension of an existing 2D fully convolutional neural network, adding dropout layers to the encoder and decoder blocks. This approach has more computational requirements than deterministic inference; it is still possible to perform offline or batch quality control in an industrial setting where reliability is essential [50].

3.5.3. Operational efficacy

In practice, automated quality control using measures of uncertainty minimizes manual inspection, relies on continuous (not binary) quality reports, and allows specified human inspection of cases with high uncertainty. The same can be extended to additional segmentation and classification manufacturing tasks, enabling scalable, reliable automated inspection.

The aggregate of the case studies appearing shows the disruptive nature of CV applications in the field of smart manufacturing quality control (Table 1). Several important themes and issues arise, as follows:

- **Adaptability and data efficiency:** techniques such as transfer learning and continual adaptation are critical for rapid deployment and sustained performance as products, processes, and defect profiles evolve.
- **Scalability and system integration:** both fog and edge-cloud architectures can provide the type of effective system integration that supports the legacy automation systems, multifarious hardware platforms, and strict real-time demands.
- **Reliability and trust:** the key to going beyond black box automation is the estimation of uncertainty and the Bayesian approach that will allow making decisions informed by confidence and selective human intervention.
- **Human-in-the-loop:** huge advances in automation still require human intervention to observe, interpolate, and give a response to a complex or contradictory case. Computer vision systems are also becoming decision-support tools and are used to supplement Human expertise, rather than replace it.
- **Resource and operational constraints:** on-the-fly inference, privacy, and the cost of communication demand that the complexity of the model, mechanism of deployment, and system coordination have to be well-balanced.

Table 1. Comparative summary table for the computer vision approach

Technology / Approach	Key Features	Advantages	Limitations	Influence on Smart Manufacturing
Deep Learning + Fog Computing	CNNs deployed on local fog nodes	Low latency, high precision	Complex maintenance, hardware cost	Enables real-time inspection and rapid response
Transfer Learning	Reuse of pretrained models	Faster training, adaptable	Domain bias, limited novelty	Supports flexible product-line updates
Edge-Cloud Collaboration	Hybrid architecture	Scalable, continuous learning	Network dependency	Balances speed and performance for robotic inspection
Real-Time Object Detection	YOLO-based models	Operational visibility, bottleneck analysis	Sensitive to lighting and camera setup	Improves productivity and process transparency
Bayesian Deep Learning	Probabilistic inference with uncertainty metrics	Reliable decision-making, human-in-loop	Computationally heavy	Enhances trust and explainability in AI-driven QC

In general, models such as Bayesian QuickNAT can be regarded as a significant innovation in automated quality control processes. It is, however, significant that the two advanced computational and human interventions are combined to ensure quality assurance that can be anticipated and scaled in a manufacturing situation.

4. Conclusions

The paper has identified the holistic use of CV to attain automation, precision, and dependability in smart manufacturing. It is new in that it combines investigative, architectural, and active viewpoints crossways numerous AI-based methods, including deep learning and transmission education, as well as Bayesian implication and hybrid edge-cloud methods [51]. The study results, through a relative examination, control the aids of each approach to manufacturing intelligence, adaptive knowledge, and procedure optimization. On the one hand, the CV, which is progressively big data-based and eased by progressive AI and rigid mathematical outlines, is rapidly rotating into the forefront of the smart engineering segment of automatic quality regulator, control, and performance testing [52]. Done cautious analysis of real-world requests, one would have understood that deep learning, transfer learning, numerous edge/fog/cloud calculations, and Bayesian-based plans for

counting doubt are all being used to make a more dependable, scalable, and flexible system of quality declaration.

The aptitude to enlarge the application can be attained through this planned location by leveraging inspection-based machine learning. Additional methods comprise transfer learning, data increase, and others. Also important in easing the burden of data shortage, these schemes hasten the transition to new mechanisms and faults [53]. Dispersed constructions, such as LAECIPS, also prove how edge and cloud capitals can be traded off in contradiction to predictive system latency presentation. Value has been prolonged through convolutional neural networks. Control within the scope of working analytics requests that help perceive objects, track them in real time, and classify process disorganizations. In the interim, Bayesian deep learning offers an honorable methodology and doubt estimation, allowing explainable and vigorous automated quality control.

Despite these innovations, it has several limitations. The article is based on secondary data and case studies versus experimentation. Also, other issues, such as system interoperability, are high. Some of the challenges it has faced include computational costs, data privacy, and large-scale adoption. The future study should endeavor to develop light but explicable AI models and self. Adaptable CV systems that can be easily incorporated into existing industrial systems. Nonetheless, several challenges persist. In combination with old equipment, the guarantee of real-time performance predictability, handling of communication and data privacy limitations, and the development of effective collaboration between a human and a machine are active fields of research and development.

Declaration of competing interest

The authors declare that they have no known financial or non-financial competing interests in any material discussed in this paper.

Funding information

No funding was received from any financial organization to conduct this research.

Author contribution

The contribution to the paper is as follows: O. Suprun, D. Korotin: study conception and design; D. Korotin, K. Kravchenko, G. Goryachev: data collection; O. Suprun, K. Kravchenko, G. Goryachev, A. Tverdokhlib: analysis and interpretation of results; A. Tverdokhlib: draft preparation. All authors approved the final version of the manuscript.

References

- [1] E. V. Filho, L. Lang, M. L. Aguiar, et al., “Computer vision as a tool to support quality control and robotic handling of fruit: a case study”, *Applied Sciences*, vol. 14, no. 21, p.9727, 2024. <https://doi.org/10.3390/app14219727>
- [2] M. Galindo-Salcedo, A. Pertúz-Moreno, S. Guzmán-Castillo, Y. Gómez-Charris, and A. R. Romero-Conrado, “Smart manufacturing applications for inspection and quality assurance processes”, *Procedia Computer Science*, vol. 198, pp. 536–541, 2022. <https://doi.org/10.1016/j.procs.2021.12.282>
- [3] N. Stelmakh, I. Mastenko, O. Sulima, and T. Rudyk, “Features of the implementation of computer vision in the problems of automated product quality control”, *Informatyka, Automatyka, Pomiary w Gospodarce i Ochronie Środowiska*, vol. 13, 2023. <https://doi.org/10.35784/iapgos.3434>
- [4] M. R. Islam, et al., “Deep learning and computer vision techniques for enhanced quality control in manufacturing processes”, *IEEE Access*, 2024. <https://doi.org/10.1109/ACCESS.2024.3453664>

-
- [5] M. Bostrom, “An evaluation of computer vision and cloud computing integration for automated quality control in smart factories”, *Uppsala University Publications*, 2025. [Online]. Available: <https://uu.divaportal.org/smash/get/diva2:1926018/FULLTEXT01.pdf>
- [6] H. M. Hubal, “The generalized kinetic equation for symmetric particle systems”, *Mathematica Scandinavica*, vol. 110, no. 1, p. 140, 2012. <https://doi.org/10.7146/math.scand.a-15201>
- [7] A. Mazakova, S. Jomartova, W. Wójcik, T. Mazakov, and G. Ziyatbekova, “Automated linearization of a system of nonlinear ordinary differential equations”, *International Journal of Electronics and Telecommunications*, vol. 69, no. 4, pp. 655-660, 2023. <https://doi.org/10.24425/ijet.2023.147684>
- [8] V. Vlasenko, et al., “Devising a procedure for the brightness alignment of astronomical frames background by a high frequency filtration to improve accuracy of the brightness estimation of objects”, *Eastern-European Journal of Enterprise Technologies*, vol. 2, no. 2 (128), pp. 31–38, 2024. <https://doi.org/10.15587/1729-4061.2024.301327>
- [9] J. Silva, et al., “Validating the use of smart glasses in industrial quality control: A case study”, *Applied Sciences*, vol. 14, no. 5, p. 1850, 2024. <https://doi.org/10.3390/app14051850>
- [10] J. O. Awujoola et al., “Machine learning–enabled predictive analytics for quality assurance in Industry 4.0 and smart manufacturing: A case study on red and white wine quality classification”, in *Industry 4.0, Smart Manufacturing, and Industrial Engineering*, Boca Raton, FL, USA: CRC Press, 2024, pp. 65–97. <https://doi.org/10.1201/9781003473886>
- [11] E. Hadzhyiev et al., “Application of Docker Compose for Constructing the Infocommunication System for Online Processing of Astronomical Images”, In *Proceedings of the IEEE International Conference on Advanced Computer Information Technologies*, pp. 629–633, 2025. <https://doi.org/10.1109/acit65614.2025.11185586>
- [12] L. Yang, R. Kumar, R. Kaur, et al., “Exploring the role of computer vision in product design and development: A comprehensive review”, *International Journal on Interactive Design and Manufacturing (IJIDeM)*, vol. 18, no. 6, pp. 3633–3680, 2024. <https://doi.org/10.1007/s12008-024-01765-7>
- [13] A. K. Tyagi, P. Bhatt, N. Chidambaram, and S. Kumari, “Artificial intelligence-empowered smart manufacturing for modern society: A review”, in *Artificial Intelligence-Enabled Digital Twin for Smart Manufacturing*, 2024, pp. 55–83. <https://doi.org/10.1002/9781394303601>
- [14] A. Trubetskaya, A. Ryan, and F. Murphy, “An implementation model for digitisation of visual management to develop a smart manufacturing process”, *International Journal of Lean Six Sigma*, vol. 15, no. 8, pp. 32–49, 2024. <https://doi.org/10.1108/IJLSS-07-2022-0156>
- [15] V. Vlasenko, et al., “Development of a procedure for fragmenting astronomical frames to accelerate high frequency filtering”, *Eastern-European Journal of Enterprise Technologies*, vol. 3, no. 9 (129), pp. 70–77, 2024. <https://doi.org/10.15587/1729-4061.2024.306227>
- [16] J. Simon and L. Gogolák, “Supply chain management using automatic guided vehicle systems in smart factory logistics”, in *Proc. Int. Conf. Central European Infrastructure Protection*, Cham, Switzerland: Springer Nature, 2024, pp. 611–624. https://doi.org/10.1007/978-3-031-78544-3_49
- [17] A. Kabdoldina, et al., “Development of the design and technology for manufacturing a combined fiber-optic sensor used for extreme operating conditions”, *Eastern-European Journal of Enterprise Technologies*, vol. 5, no. 5 (119), pp. 34-43, 2022. <https://doi.org/10.15587/1729-4061.2022.266359>
- [18] S. Khlamov, et al., “Comparative analysis of JMeter and Postman for API-based performance testing”, *CEUR Workshop Proceedings*, vol. 3790, pp. 426–440, 2025. <https://ceur-ws.org/Vol-4048/paper34.pdf>
-

-
- [19] V. Savanevych, et al., “Mathematical methods for an accurate navigation of the robotic telescopes”, *Mathematics*, Special issue “Mathematics in Robot Control for Theoretical and Applied Problems”, vol. 11(10), 2246, 2023. <https://doi.org/10.3390/math11102246>
- [20] H. M. Ahmad, A. Rahimi, and K. Hayat, “Capacity constraint analysis using object detection for smart manufacturing”, *arXiv preprint*, 2402.00243, 2024. <http://arxiv.org/pdf/2402.00243v1>
- [21] A. Guha Roy, S. Conjeti, N. Navab, and C. Wachinger, “Bayesian QuickNAT: Model uncertainty in deep whole-brain segmentation for structure-wise quality control”, *arXiv preprint*, 1811.09800, 2018. <http://arxiv.org/pdf/1811.09800v1>
- [22] M. Hussain, “Sustainable machine vision for Industry 4.0: A comprehensive review of convolutional neural networks and hardware accelerators in computer vision”, *AI*, vol. 5, no. 3, pp. 1324–1356, 2024. <https://doi.org/10.3390/ai5030064>
- [23] W. Zhai, Q. Han, L. Chen, and X. Shi, “Explainable AutoML (xAutoML) with adaptive modeling for yield enhancement in semiconductor smart manufacturing”, in *Proc. 2nd Int. Conf. Artificial Intelligence and Automation Control (AIAC)*, 2024, pp. 162–171, IEEE. <https://doi.org/10.1109/AIAC63745.2024.10899729>
- [24] A. Taatali, S. E. Sadaoui, M. A. Louar, and B. Mahiddini, “On-machine dimensional inspection: Machine vision-based approach”, *The International Journal of Advanced Manufacturing Technology*, vol. 131, no. 1, pp. 393–407, 2024. <https://doi.org/10.1007/s00170-024-13081-1>
- [25] V. Akhmetov, et al., “Cloud computing analysis of Indian ASAT test on March 27, 2019”, in *Proc. IEEE International Scientific and Practical Conference "Problems of Infocommunications. Science and Technology"*, 2019, pp. 315–318, IEEE. <https://doi.org/10.1109/PICST47496.2019.9061243>
- [26] H. Chen, et al., “Human-in-the-loop robot learning for smart manufacturing: A human-centric perspective”, *IEEE Transactions on Automation Science and Engineering*, 2025. <https://doi.org/10.1109/TASE.2025.3528051>
- [27] M. Peruzzini, E. Prati, and M. Pellicciari, “A framework to design smart manufacturing systems for Industry 5.0 based on human-automation symbiosis”, *International Journal of Computer Integrated Manufacturing*, vol. 37, no. 10–11, pp. 1426–1443, 2024. <https://doi.org/10.1080/0951192X.2023.2257634>
- [28] D. J. Powell, “Artificial intelligence in lean manufacturing: Digitalization with a human touch?”, *International Journal of Lean Six Sigma*, vol. 15, no. 3, pp. 719–729, 2024. <https://doi.org/10.1108/IJLSS-05-2024-256>
- [29] M. F. B. Shaikat, “Pilot deployment of an AI-driven production intelligence platform in a textile assembly line”, *Authorea Preprints*, 2025. <https://doi.org/10.36227/techrxiv.175203708.81014137/v1>
- [30] H. M. Hubal, “The convergence of the series of the solution of the Cauchy problem for the bbgky hierarchy of equations in many-kind particle systems”, *International Journal of Pure and Applied Mathematics*, vol. 108, no. 4, 2016. <https://doi.org/10.12732/ijpam.v108i4.20>
- [31] R. Rakholia, et al., “Advancing manufacturing through artificial intelligence: Current landscape, perspectives, best practices, challenges, and future direction”, *IEEE Access*, 2024. <https://doi.org/10.1109/ACCESS.2024.3458830>
- [32] F. Lupi, A. Maffei, and M. Lanzetta, “CAD-based autonomous vision inspection systems”, *Procedia Computer Science*, vol. 232, pp. 2127–2136, 2024. <https://doi.org/10.1016/j.procs.2024.02.033>
-

-
- [33] V. Savanevych, et al., “Formation of a typical form of an object image in a series of digital frames”, *Eastern-European Journal of Enterprise Technologies*, vol. 6, no. 2-120, pp. 51–59, 2022. <https://doi.org/10.15587/1729-4061.2022.266988>
- [34] T. Kliestik, P. Kral, M. Bugaj, and P. Durana, “Generative artificial intelligence of things systems, multisensory immersive extended reality technologies, and algorithmic big data simulation and modelling tools in digital twin industrial metaverse”, *Equilibrium*, vol. 19, no. 2, 2024. <https://doi.org/10.24136/eq.3108>
- [35] N. Smailov, et al., “Simulation and Measurement of Strain Waveform under Vibration Using Fiber Bragg Gratings”, *Sensors*, vol. 24, no. 19, Article 6194, 2024. <https://doi.org/10.3390/s24196194>
- [36] V. Goyal, A. Yadav, and R. Mukherjee, “A literature review on the role of Internet of Things, computer vision, and sound analysis in a smart poultry farm”, *ACS Agricultural Science & Technology*, vol. 4, no. 4, pp. 368–388, 2024. <https://doi.org/10.1021/acsagscitech.3c00467>
- [37] J. John, et al., “Industry 4.0 and beyond: The role of 5G, Wi-Fi 7, and time-sensitive networking (TSN) in enabling smart manufacturing”, *Future Internet*, vol. 16, no. 9, p. 345, 2024. <https://doi.org/10.3390/fi16090345>
- [38] P. Mikhailov, Z. Ualiyev, A. Kabdoldina, N. Smailov, A. Khikmetov, and F. Malikova, “Multifunctional fiber-optic sensors for space infrastructure”, *Eastern-European Journal of Enterprise Technologies*, vol. 5, no. 5 (113), pp. 80-89, 2021. <https://doi.org/10.15587/1729-4061.2021.242995>
- [39] M. S. Ahmmed, S. P. Isanaka, and F. Liou, “Promoting synergies to improve manufacturing efficiency in industrial material processing: A systematic review of Industry 4.0 and AI”, *Machines*, vol. 12, no. 10, p. 681, 2024. <https://doi.org/10.3390/machines12100681>
- [40] N. Su, S. Huang, and C. Su, “Elevating smart manufacturing with a unified predictive maintenance platform: The synergy between data warehousing, Apache Spark, and machine learning”, *Sensors*, vol. 24, no. 13, p. 4237, 2024. <https://doi.org/10.3390/s24134237>
- [41] V. Khlamov, et al., “Development of the matched filtration of a blurred digital image using its typical form”, *Eastern-European Journal of Enterprise Technologies*, vol. 1, no. 9-121, pp. 62–71, 2023. <https://doi.org/10.15587/1729-4061.2023.273674>
- [42] A. Ercetin et al., “Review of image processing methods for surface and tool condition assessments in machining”, *Journal of Manufacturing and Materials Processing*, vol. 8, no. 6, p. 244, 2024. <https://doi.org/10.3390/jmmp8060244>
- [43] L. S. Goecks, A. F. Habekost, A. M. Coruzzolo, and M. A. Sellitto, “Industry 4.0 and smart systems in manufacturing: Guidelines for the implementation of a smart statistical process control”, *Applied System Innovation*, vol. 7, no. 2, p. 24, 2024. <https://doi.org/10.3390/asi7020024>
- [44] M. Singh et al., “Unity and ROS as a digital and communication layer for digital twin application: Case study of robotic arm in a smart manufacturing cell”, *Sensors*, vol. 24, no. 17, p. 5680, 2024. <https://doi.org/10.3390/s24175680>
- [45] A. N. Beskopylny, J. Kapukotuwa, E. L. S. Gouveia, E. Fuenmayor, Y. Qiao, N. Murray, and D. Devine, “Computer vision method for automatic detection of microstructure defects of concrete”, *Sensors*, vol. 24, no. 13, p. 4373, 2024. <https://doi.org/10.3390/s24134373>
- [46] P. Visconti, et al., “Machine learning and IoT-based solutions in industrial applications for smart manufacturing: A critical review”, *Future Internet*, vol. 16, no. 11, p. 394, 2024. <https://doi.org/10.3390/fi16110394>
-

-
- [47] I. Izquierdo-Bueno, et al., “Smart viniculture: Applying artificial intelligence for improved winemaking and risk management”, *Applied Sciences*, vol. 14, no. 22, p. 10277, 2024. <https://doi.org/10.3390/app142210277>
- [48] E. Kristiani, et al., “An intelligent thermal compensation system using edge computing for machine tools”, *Sensors*, vol. 24, no. 8, p. 2531, 2024., <https://doi.org/10.3390/s24082531>
- [49] I. Rojek, J. Kopowski, J. Lewandowski, and D. Mikołajewski, “Use of machine learning to improve additive manufacturing processes”, *Applied Sciences*, vol. 14, no. 15, p. 6730, 2024. <https://doi.org/10.3390/app14156730>
- [50] B. Maljugić, D. Čoćkalo, M. Bakator, and S. Stanisavljev, “The role of the quality management process within Society 5.0”, *Societies*, vol. 14, no. 7, p. 111, 2024. <https://doi.org/10.3390/soc14070111>
- [51] T. Komenda, N. Komenda, and Y. Vagapov, “Criteria of morphometric analysis of a daily load profile”, *International Transactions on Electrical Energy Systems*, vol. 29, no. 5, Article e2847, 2019.
- [52] S. Khlamov, M. Mendieliava, O. Vovk, and Zh. Deineko, “Comparative analysis of JMeter and Postman for API-based performance testing”, *CEUR Workshop Proceedings*, vol. 4048, pp. 426-440, 2025. <https://ceur-ws.org/Vol-4048/paper34.pdf>
- [53] H. Khudov, P. Mynko, S. Ikhsanov, et al., “Development of a method for determining the coordinates of air objects by radars with the additional use of multilateration technology”, *Eastern-European Journal of Enterprise Technologies*, vol. 5, no. 9 (113), pp. 6-16, 2021. <https://doi.org/10.15587/1729-4061.2021.242935>